

The Green Products Company

"Building A Greener Tomorrow!"

A DIVISION OF ACOUSTICAL SURFACES, INC.

123 Columbia Court North ■ Suite 201 ■ Chaska, MN 55318
 (952) 448-5300 ■ Fax (952) 448-2613 ■ (800) 708-0517

Email: sales@thegreenproductscompany.com
 Visit our Website: www.thegreenproductscompany.com



ECOGLUE EXTREME

GREEN QUALITIES:

- Insulation value of 4.8R per inch
- Fiberglass free
- Formaldehyde free
- No skin Irritation


DESCRIPTION:

ECOGLUE™ EXTREME is a high performance polyether moisture cure technology that is 100% solids, solvent free and less than 2% VOC. Environmentally friendly without sacrificing strength. It's engineered for strong adhesion to virtually any substrate, and will provide a long lasting weather tight seal even in the most unfavorable wet application conditions. EcoGlue Extreme is suitable for vertical or overhead applications and can be painted after 24 hours. It is safe to use indoors, or in confined spaces, as it contains no odor. Best application temperatures are above 30 F (-1 C). Moisture Cure / Odor Free / Non-Shrink / Instant Grab / Flexible /Waterproof / Paintable.

PRODUCT BENEFITS/SUBSTRATES:

Product Benefits	Substrates	Product Benefits	Substrates
Moisture Cure Technology	Concrete	Elastic/Flexible	Aluminum
100% Solids/Non Shrink or Crack	Block	No Mixing-Single Component	PVC
No Solvents/No Outgassing	Brick	Waterproof	SBS Mod Bit
Less than 2% VOC	Stone	Excellent Weathering Properties	EPDM
No Prop 65 Materials	Wood	Provides Temporary Emergency Underwater Repair	Many Engineering Plastics
No Odor	Cement Fiber Board	Formaldehyde Free	Vinyl
Non-Sag/Applies Vertically & Horizontally	Masonry (Bonds to Damp Masonry)	UV Stable	Glass
Instant Grab	Galvanized Metal	Paintable	Foam
		Dries White	& More

Continued on next page...



The Green Products Company

"Building A Greener Tomorrow!"

A DIVISION OF ACOUSTICAL SURFACES, INC.

123 Columbia Court North ■ Suite 201 ■ Chaska, MN 55318
(952) 448-5300 ■ Fax (952) 448-2613 ■ (800) 708-0517

Email: sales@thegreenproductscompany.com

Visit our Website: www.thegreenproductscompany.com

INDUSTRY USES:

Truck/Bus/Metro/RV, Manufactured Housing, Construction, (Residential/Commercial), Light Trailers, Metal Buildings, Steel Roofing, Steel Entry Doors.

PRODUCT DATA:

Packaging Specs:

Sales Part #: 575012

Size: 10.1 Oz. Cartridge

Case Weight: 15.0 lbs.

Case Dims: 7.94 in. x 5.94 in. x 11.25 in. (L(depth) x W X H)

Case Cube: 0.31 ft.3

Case Pack: 12

FLAMMABILITY:

ASTM E 84 Flame Spread 20 , Smoke Generation 180

HOW TO USE:

- Make sure surfaces are clean and free of dirt, oil or debris.
- Clean contaminated surfaces with alcohol, not petroleum based solvents.
- A quality caulking gun is recommended to ensure ease of application.
- Best when used above 30° F (-1°C)
- Cut cartridge tip to desired size at a 45° angle, and puncture foil seal with nail.
- Begin gunning to bond surfaces and assemble, making sure bonded materials are tightly joined.
- Use mechanical fasteners as needed or dry tool the sealant to create a strong mechanical bond against the joint faces.
- **NOTE:** *Application specific instructions provided on Technical Data Sheet.*

CURING:

EcoGlue™ Extreme has instant grab, typically skins over within 35 minutes, and cures completely in 3 to 7 days depending upon temperature, humidity and thickness. Lower temperatures and humidity prolong cure time. Higher temperatures accelerate cure time.

CLEANUP:

Wet sealant can be removed using a solvent such as alcohol or soap and water. Cured product can be removed by abrading or scraping the substrate.

STORAGE:

Store in original unopened containers and in a cool dry area. Protect container from heat and direct sunlight. Elevated temperatures will reduce shelf life.